

EXAFOAM

Closed-Cell Polyethylene Fillerboard

DESCRIPTION

EXOFOAM is a closed cell polyethylene foam fillerboard for use in expansion joints in concrete. Its closed cell structure makes the product non-absorbent and easily compressed.

USES

EXAFOAM is a compressible joint filler board, used as a joint filler in masonry and concrete structures to provide a back of the joint sealant.

ADVANTAGES

- Excellent compressibility.
- Closed cell structure prevents water absorption.
- Easily cut to shape.

Property	Value
Elongation @ Break	80%
Tensile Strength	2.5 kN/cm
Recovery from Compression	>70%

PROCEDURE

Application: EXAFOAM is typically bonded to an existing structure or previously poured concrete slab using a suitable contact adhesive. If the joint is to be sealed using a joint sealant then a plastic strip joint former should be placed on top of the EXAFOAM which is removed once the concrete is poured to form a rebate for the sealant to fill.

PACKAGING & COVERAGE

EXOFOAM is supplied in 1 M x 2 M sheets at the following thicknesses, 10mm, 15mm, 20mm, 25mm and 30mm.

STORAGE

EXOFOAM should be stored in clean dry conditions away from direct sunlight.

HEALTH & SAFETY

See separate material safety datasheet.

The information provided in this data sheet is intended for general guidance only and is given in good faith based on FIS Construction Products' current knowledge and experience. No warranty in respect of fitness for a purpose, or any other liability whatsoever can be inferred from the information contained within this datasheet. Users should determine the suitability of the materials for their particular application and should always refer to the most recent issue of the product data sheet for the product concerned. All materials are supplied in accordance with FIS Construction Products Sales Terms & Conditions (available upon request and on Company Website)