

EPOPRIME MMA- BASE

1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY

1.1 Product Identifier Epoprime MMA- Base

1.2 Relevant identified uses of the substance or mixture and uses advised against:

[SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites; [PC9a] Coatings and paints, thinners, paint removers; [PROC10] Roller application or brushing;

1.3 Details of the supplier of the data sheet

FIS Construction Products
Seymour House
Mayflower Close
Chandlers Ford
Eastleigh
Hampshire
SO53 4AR

sales@fisproducts.co.uk
www.fisproducts.co.uk

Emergency telephone number
+44 (0) 800 6191619
7.00am-5:00pm Mon-Fri

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

2.1.1 Classification - F; R11 Xi; R37/38-43
1999/45/EC Symbols: F: Highly flammable. Xi: Irritant.

Main hazards Highly flammable. Irritating to respiratory system and skin. May cause sensitisation by skin contact.

2.1.2 Classification – EC Flam. Liq. 2: H225; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 3: H335; 1272/2008

2.2 Label elements

Hazard pictograms



Signal Word	Danger
Hazard Statement	Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. STOT SE 3: H335 - May cause respiratory irritation.
Precautionary Statement: Prevention	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground/bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/lighting// equipment. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	P302+P352 - IF ON SKIN: Wash with plenty of water/ . P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 - Call a POISON CENTER/doctor/ /if you feel unwell. P321 - Specific treatment (see on this label). P332+P313 - If skin irritation occurs: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P370+P378 - In case of fire: Use to extinguish.
Precautionary Statement: Storage	P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to

3. COMPOSITION INFORMATION ON INGREDIENTS

3.1 Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Methyl methacrylate	607-035-00-6	80-62-6	201-297-1	01-2119452498-28	40 - 50%	F; R11 Xi; R37/38 R43	
N,N-bis-(2-hydroxypropyl)-p-toluidine		38668-48-3	254-075-1		0 - 0.5%		
N,N-Dimethyl-p-toluidine	612-056-00-9	99-97-8	202-805-4		0 - 0.5%	T; R23/24/25 R33 R52/53	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Methyl methacrylate	607-035-00-6	80-62-6	201-297-1	01-2119452498-28	40 - 50%	Flam. Liq. 2: H225; STOT SE 3: H335; Skin Irrit. 2: H315; Skin Sens. 1: H317;	
N,N-bis-(2-hydroxypropyl)-p-toluidine		38668-48-3	254-075-1		0 - 0.5%		
N,N-Dimethyl-p-toluidine	612-056-00-9	99-97-8	202-805-4		0 - 0.5%	Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT RE 2: H373; Aquatic Chronic 3: H412;	

4. FIRST AID MEASURES

4.1 Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing.
Ingestion	DO NOT INDUCE VOMITING. Drink 1 to 2 glasses of water.

4.2 Most important symptoms and effects, both acute and delayed

Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.
Eye contact	Irritating to eyes.
Skin contact	Irritating to skin.
Ingestion	Ingestion may cause nausea and vomiting.

4.3 Indication of any immediate medical attention and special treatment needed

Inhalation	Seek medical attention.
Eye contact	Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Seek medical attention.

5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media Carbon oxides. Dry chemical. Foam. Do NOT use water jet.

5.2 Special hazards arising from the substance or mixture

Highly flammable. Burning produces irritating, toxic and obnoxious fumes. Vapour may travel considerable distance to source of ignition and flash back.

5.3 Advice for firefighters Self-contained breathing apparatus. Wear protective clothing.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Wear suitable protective equipment. Eliminate all sources of ignition. Evacuate personnel to a safe area. Wear suitable respiratory equipment when necessary.

6.2 Environmental precautions Do not allow product to enter drains. Prevent further spillage if safe.

6.3 Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water. Use explosion proof equipment.

6.4 Reference to other sections

See section 8 for further information.
See section 13 for further information.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking. Vapours are heavier than air.

7.2 Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers. Store in original container.

7.3 Specific end use(s) See section 1.2 for further information.

8. EXPOSURE CONTROL AND PROTECTION MEASURES

8.1 Control parameters

8.1.1 Exposure Limit Values

Methyl methacrylate	WEL 8-hr limit ppm: 50	WEL 8-hr limit mg/m ³ : 208
	WEL 15 min limit ppm: 100	WEL 15 min limit mg/m ³ : 416
	WEL 8-hr limit mg/m ³ total inhalable dust: -	WEL 15 min limit mg/m ³ total inhalable dust: -
	WEL 8-hr limit mg/m ³ total respirable dust: -	WEL 15 min limit mg/m ³ total respirable dust: -

8.2 Exposure controls



8.2.1	Appropriate engineering Controls	Ensure adequate ventilation of the working area.
8.2.2	Individual protection measures	Wear chemical protective clothing.
	Eye / face protection	Approved safety goggles.
	Skin protection - Handprotection	Chemical resistant gloves (PVC). Butyl rubber gloves.
	Skin protection - Other	Wear suitable protective clothing.
	Respiratory protection	Wear suitable respiratory equipment when necessary.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	Liquid
Colour	Colourless
Odour	Strong/Characteristic
Odour threshold	No data available
pH	No data available
Melting point	No data available
Freezing Point	-48 °C
Initial boiling point	> 100 °C
Flash point	10 °C
Evaporation rate	No data available
Flammability (solid, gas)	No data available

Upper Explosive Limit	12.5 %
Lower Explosive Limit	2.1 %
Vapour pressure	No data available
Vapour density	> 1 g/cm ³
Relative density	No data available
Fat Solubility	No data available
Partition coefficient	No data available
Autoignition temperature	430 °C
Viscosity	200 mPas (Cone & Plate)
Explosive properties	No data available
Oxidising properties	No data available
Solubility	Slightly soluble in water

9.2 Other information

Conductivity	No data available
Surface tension	No data available
Gas group	No data available
Benzene Content	0 %
Lead content	0 %
VOC (Volatile organic compounds)	0 g/l

10. STABILITY AND REACTIVITY

10.1	Reactivity	See section 10.2 for further information.
10.2	Chemical stability	Stable under normal conditions.
10.3	Possibility of hazardous reactions	Oxidising agents.
10.4	Conditions to avoid	Heat, sparks and open flames.
10.5	Incompatible materials	Alkalis. Oxidising agents. Peroxides. Reducing agents. Sulphur oxides.
10.6	Hazardous decomposition products	Will not decompose if stored and used as recommended.

11. TOXOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity	Oral Rat LD50 = >5,000mg/kg (Methyl Methacrylate).
Skin corrosion/irritation	Irritating to skin.
Serious eye damage/irritation	Irritating to eyes.
Respiratory or skin sensitisation	May cause sensitisation by skin contact.

Germ cell mutagenicity	No mutagenic effects reported.
Carcinogenicity	No carcinogenic effects reported.
Reproductive toxicity	No observed effect level. No teratogenic effects reported.
Aspiration hazard	No Significant Hazard.

11.2 Toxicological Information

Methyl methacrylate	Dermal Rat LD50: >5,000mg/kg	Oral Rat LD50: >2,000mg/kg
	Dermal Rabbit LD50: >5,000mg/kg	Inhalation Rat LC50/4 h: 29.8mg/kg
N,N-bis-(2-hydroxypropyl)-p-toluidine	Oral Rat LD50: 172mg/kg	

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Methyl methacrylate	Daphnia EC50/48h: 69.0000 mg/l	Fish LC50/96h: 79.0000 mg/l
---------------------	--------------------------------	-----------------------------

12.2 Persistence and degradability Readily biodegradable. OECD 301C, 14D.

12.3 Bioaccumulative potential No observed effect level.

Partition coefficient Epoprime MMA - Base No data available

12.4 Mobility in soil Slightly soluble in water.

12.5 Results of PBT and vPvB assessment PBT no. vPvB no.

12.6 Other adverse effects No data is available on this product.

13. DISPOSAL CONSIDERATIONS

General information

08 01 11* waste paint and varnish containing organic solvents or other dangerous substances.

Disposal methods

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. Waste packaging should be recycled if possible. Incineration should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned. Empty containers or liners may still contain residue. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Disposal of packaging

Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

14. TRANSPORT INFORMATION

Hazard pictograms



14.1	UN number	UN1866
14.2	UN proper shipping name	RESIN SOLUTION ((Methyl Methacrylate))
14.3	Transport hazard class(es)	
	ADR/RID	3
	Subsidiary risk	-
	IMDG	3
	Subsidiary risk	-
	IATA	3
	Subsidiary risk	-
14.4	Packing group	
	Packing group	II
14.5	Environmental hazards	
	Environmental hazards	No
	Marine pollutant	No
14.6	Special precautions for user	Not applicable.
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	
		Not applicable.
	ADR/RID	
	Hazard ID	33
	Tunnel Category	(D/E)
	IMDG	
	EmS Code	F-E S-E

IATA

Packing Instruction (Cargo)	364
Maximum quantity	60 L
Packing Instruction (Passenger)	353
Maximum quantity	5 L

Further information

The product is not classified as dangerous for carriage.

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

15.2 Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

16. OTHER INFORMATION

Other information

Text of risk phrases in Section 3

R11 - Highly flammable.
R23/24/25 - Toxic by inhalation, in contact with skin and if swallowed.
R33 - Danger of cumulative effects.
R37/38 - Irritating to respiratory system and skin.
R43 - May cause sensitisation by skin contact.
R52/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Text of Hazard Statements in Section 3	Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. STOT SE 3: H335 - May cause respiratory irritation. Acute Tox. 3: H301 - Toxic if swallowed. Acute Tox. 3: H311 - Toxic in contact with skin. Acute Tox. 3: H331 - Toxic if inhaled. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Maximum content of VOC	0 g/l.
Further information	

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.

The above information is believed to be correct but not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the product.